POP	Supl. Model	Picture	Sisteme Alarmi	
			Alarm Vjedhje Me Kabell "PMA"	
2.20	ALVP-1	RM	Central Alarmi. Kaptain Pima	
2.20	ALVP-2	ENAL STATE OF THE	Tastiere Alarmi. RX406 * 6 zone LEDs display * 5 system status LEDs * For CAPTAIN-i only (ver 4.0 and up)	
2.20	ALVP-3	Part of the state	Tastiere Alarmi LCD. RX400. * 6 zone LEDs display. * 5 system status LEDs * For CAPTAIN-i only (ver 4.0 and up)	
2.20	ALVP-4		Sirene e Jashtme TK81	
2.20	ALVP-5		Sirene e Jashtme With Backup Bateri	
2.20	ALVP-6		Sirene e Brendshme	
2.20	ALVP-7		Digi P-Rex Digital PIR detector, Spherical lens, coverage angle 89-110, Range 0,3 - 15m. Crep zone:0,3m coverage0.3 to 15m. Adaptive pulse count 1,2 or 3. RFI immunity. Temperature compensation. Operating temperature -20° / + 60°C. Me Krah	
2.20	ALVP-8		Pet Imune Sensor 201 Pet	
2.20	ALVP-9		Smoke Sensor	
2.20	ALVP-10		Smoke Sensor With Relay	
2.20	ALVP-11	4	Magnetic Contact	
2.20	ALVP-12		Glas Break Senor (Njekohesisht dhe siamic sensor)	

2.20	ALVP-13		Beem Detector 40m
2.20	ALVP-14	111	Mic-200-Voice Module
2.20	ALVP-15		Voice message unit
2.20	ALVP-16	ENT	GSM Module
2.20	ALVP-17		REMOTE Control Unit + Pult
2.20	ALVP-18		Panic Button
			Alarm Wireless (Pa Kabell) Visionic Tel / GSN
			PWRMAX PRO (868) PRT P5 KIT.
1.70	0-101586		High-end, modular design Self contained; no need for external boxes Multiple optional built-in modules: Internal PowerLink module enables camera connectivity for
1.50	0-101925	Custon Service Control of the Contro	PowerMax Express P2 ENG (868) INT PS. Built-in PSTN communicator Stylish, ultra-compact design, fits any décor Versatile communications capabilities: Built-in PSTN communicator Easy-to-add internal GSM/GPRS and/or Broadband* communications modules for maximum alarm reporting
			PWRMAX COMPLETE (868) KIT W/O VOICE . Versatile communications capabilities:
1.50	0-100523		Built-in PSTN communicator. Easy-to-add internal GSM/GPRS and/or IP* communications modules for maximum alarm reporting reliability to the central station and back-up for the standard.
1.50	9-101142		GSM 350/8 (900/1800MHz). Supports three data channels – GPRS*, GSM and SMS – for high-speed and highly- reliable reporting Can be configured as a backup or primary reporting method Full event reporting Recommended for every home as a backup communication line in case of line failure or system sabotage
1.50	0-101476		MKP-150 (868) PRT. Provides all the same controls, notifications, indications and voice prompts as the control panel Used to arm or disarm the security system, turn lights on and off control electrical appliances and much more

			T
1.50	0-2391-A		MCT-237 (868).
			MCT-234 (868). MCT-234 Features:
1.50	0-2381-1		Four independent functional buttons Comfortable, miniature, attractive design Superior transmission range CodeSecure encryption technology prevents unauthorized "code grabbing" MCM-140+ (868).
			MCM-140 Features:
1.50	0-2461-A	0000 0000 0000	Easy programming and user-friendly control of PowerMax system Attractive, modern, ergonomic design for hand-held use or wall mounting
			MCS-710 (868) RED. MCS-730 Features:
1.50	0-5421-A		Sleek design and high power strobe light (choice of red, blue, orange or white lens) Large free screen-print area available for company logo and information
			Next Plus MCW (868). Next+ PIR MCW Features:
1.50	0-3589-8		15m (50 ft) 90o multiple-curtain coverage with "wall" creep zone Enhanced false alarm immunity by combined Fresnel and cylindrical optics
1.50	0-101824		DISC MCW (868)
			Tower 20 AM MCW (868). TOWER-20AM MCW Features:
1.50	0-1721-0		Superior outdoor detection with virtually no false alarms Fully wireless, ideal for difficult installations Innovative Octa-Quad technology accurately determines whether motion is legitimate minimizing false alarms while
			MCT-320 (868). MCT-320 Features:
1.50	0-101046		Very small, almost invisible design Highly cost-effective for low-profile installations Fully supervised Double tamper protection (cover and wall)
			MCT-426 (868). MCT-426 Features:
1.50	0-101369		Attractive and modern design suitable for residential and commercial applications 5 or 8 years battery life (according to the battery type) and easy battery replacement

1.50	0-3648-A		MCT-441 NATURAL (868). MCT-441 Features: Detects Methane CH4 gas used for cooking and heating Transmits alerts to the control panel and provides visual and audial alerts when gas is detected
			Fully supervised detector compatible with the PowerMax
1.50	0-3645-A	- Control of the Cont	MCT-550 (868). MCT-550 Features: Detects water at ground level Ideal for basements, yachts and holiday houses
			Easy installation: includes a 3m (10ft) sensor cable for high
			nositioning of
			MCX-610 (868). Features & Benefits:
			reatures & Benefits.
1.50	0-101606	- 1	Supports both one-way and two-way keyfobs*, remote commander and all wireless PowerCode detectors Compact and easy to install
			Mains nowered with rechargeable 36-hour backun battery
1.50			
			Alarm Wireless Me GSM
3.00	ALWG-2	ENT MENTERS IN	Wireless & Wired GSM Alarm System. Model Number:G50 Events record/History record,low voltage reminder
3.00	ALWG-1	EDD D 53 -	GSM Alarm. with CE, mainly used in House, office, Factory, Shop etc.
2.60	ALWG-4	man 20 th man and the man and	GSM Home Alarm System with Photo-taken (900/1800/1900MHZ)1. Camera have back light function can work during night 3.5 group telephone numbers 4. Store pictures in SD card to store pictures 5. Work with 14 wireless detectors
2.60	ALWG-5	Just Press	MMS sending. GSM ALARM. 1.Support: 900Mhz, 1800Mhz and 1900Mhz; 2. GSM home alarm system with photo taking (900/1800/1900MHZ)Support the GSM/CDMA cell phone.
2.00	ALWG-6		GSM wireless smart alarm .Uses WAVECOM, supports the GSM/CDMA handset module, reports to the police is not been away from the limit; Brings LED to demonstrate that 1 wireless emergency call, 1 wireless fire warning defense area, 8 wireless warning defense areas, 1 external power supply warning, carries on the long-distance cloth
			Car Alarm. Me GSM
			CAR Alarm System GSM. short message/Voice long-
		6197	distance control car alarm system
2.40	ALCAG-1	8/ 38	Function:
		A27.4.0 44	Remote control
			1. Arm/disarm 2. Lock/unlock 3. Car finding 4. Trunk CAR Alarm System GSM. intelligent voiced long-
		6197	distance control car alarm system
2.40	ALCAG-2	1 98	Functions:
		37 146 99	Remote control
			1. Arm/disarm 2. Lock/unlock 3. Searching 4. Trunk release

			Alarm Wireless. Fixed Phone
4.00	ALSWF-1		FIXED Phone Alarm System. suppose 6 group of warning telephone number, to public security 110 or small-unit residential area networking warning administrative center warning, telephone call and sound recording; match each kind of wireless security detector. Brings the reserve electromagnetism, different control remotely through the telephone password deploys troops for defense and
4.00	ALSWF-2		FIXED Phone Alarm System. The product has 9 group of telephone digit dialing warning, digital LED demonstrated that 9 wireless defense areas, 10 second language sound recording, the different remote control main engine and monitors the scene situation, but seeks help urgently, the main engine power failure does not lose the information, the telephone busy when snatches the line digit dialing
4.00	ALSWF-3		Hidden alarm, telephone shape alarm system;Can be used as both telephone and alarm;28 sensors, store 6 alarm phone. Telephone Alarm System (433Mhz/315Mhz)
4.00	ALSWF-4	Tel Cn	FIXED Phone Alarm System. suppose 6 group of warning telephone number, to public security 110 or small-unit residential area networking warning administrative center warning, telephone call and sound recording; match each kind of wireless security detector. Brings the reserve
4.00	ALSWF-5	Tel Cn	FIXED Phone Alarm System. suppose 6 group of warning telephone number, to public security 110 or small-unit residential area networking warning administrative center warning, telephone call and sound recording; match each kind of wireless security detector. Brings the reserve electromagnetism, different control remotely through the telephone password deploys troops for defense and
			Simple Movement Alarm
3.80	ALSSM-1		Simple movment alarm. Me Dy Sensor dhe Nje putl
3.80	ALSSM-2	(i)	Simple movment alarm. Me Nje Sensor dhe Dy Pulta
3.20	ALSSM-3		Simple movment alarm. 1 Sensor dhe Central ne nje dhe dy pulta
			Alarm Zjarri "Mg2"
2.00	ALZM-1		Emag Panel 2. 2 Programable Zones•'Class change' facility •Enable/disable security key •one man walk test facility •Fire volt free change over relay
2.00	ALZM-2		Sirene e Jashtme 24V

		-		
2.00	ALZM-3		Sirene e Brendshme 24V	
2.00	ALZM-4		Sensor Tymi 24V Me Baze	
2.00	ALZM-5	****	Call Piont Emergency Button	
			Alarm Gazi dhe Lageshtire	
4.20	ALGZ-1		•Gas Alarm. Power supply: 12VDC • Power and Alarm Indicator • Test Button for easily self check • Start warm-up current: ≤60mA • Static current: ≤40mA; Alarm current: ≤150mA • Static consume: ≤1W; Alarm consume: ≤1.7W	
4.20	ALWT-1		 Water Alarm. Power supply: 12VDC Static current:: ≤15MA Alarm current: ≤200MA Operating temperature: 0 - 60 °C; Dimension: 115mm*70mm*40mm 	
			Aksesore per Wireless GSM. Alarm "G2	20"
2.80	ALAW-G20		Wireless PIR Motion Detecting, Long distance wireless signal sending.	
2.80	ALAW-G21		Wireless Magnetic Contact Sensor for CAL-B2038 GSM wireless smart alarm LED Display	
2.80	ALAW-G22		Wireless . Smoke detector sensors for the GSM ALARMS (With changanble Code)	
2.80	ALAW-G23		Wireless Siren for G20E GSM Alarm	
			Wireless Accessories for Wireles & Wire	ed GSM. Alarm "G
2.80	ALAWS-50		Wireless PIR	
2.80	ALAWS-51		Wireless Magnetic Contact	

]]
2.80	ALAWS-52		Wireless Smoke Detector	
2.80	ALAWS-53		Wireless Siren	
			Wired Accessories for Wireles & Wired	GSM Alarm "G560
2.80	ALAWR-50		Wired PIR	
2.80	ALAWR-51		Wired Magnetic Contact	
2.80	ALAWR-52		Wired Smoke Detector	
2.80	ALAWR-53		Wired Siren	
			Aksesore te Ndryshem per Alarm, Wire	less
2.80	ALANWS-1		Wireless with two normal adaptors	
2.80	ALANWS-2		Wireless Glass break detector with a normal adaptor	
7.00	ALANWS-3		wireless panic button	
2.20	ALANWS-4		Wireless Gas detector	
			Aksesore te Ndryshem per Alarm, Wire	d
2.80	ALANWR-1		Wired intelligent Passive Infrared Ray, adopt close Finil lenticular technology, avoid fauls alarm. Can support Pet-proof.	
2.80	ALANWR-2		Wired. Smoke detector sensors for the wired FIRE alarm	
2.80	ALANWR-3		Wired Glass Break Sensor	

			Aksesore
1.40	ALA-1	•	12V/7,2 Ah Battery 12V/7,2Ah
2.00	ALA-5		